

# **King Pin Lock**

## Installation and Use Instructions

This **King Pin Lock** has been made from top quality materials and is designed to provide years of service. This lock should be used as a part of an overall security program to prevent theft of property and cargo.

This lock uses a positive locking, dead bolt type cylinder. The key cannot be removed from the cylinder unless it is properly locked.


**To install the lock**, slide the **King Pin Lock** fully onto the trailer King Pin. Push the lock cylinder in until it stops and turn the key counterclockwise approximately 3/4 turn to the locked position. Once properly installed and locked, the key can be removed. Rotate the lock so the lock cylinder is facing the rear of the trailer.

A helpful hint to help prevent grease from contacting the lock is to slip a plastic grocery bag through the bore of the lock and fold it over the large end of the lock.

Clip the "IN USE" Tag to the handle to prevent accidental damage by attempting to connect the trailer when the lock is in place.

**To remove the lock**, insert the key into the lock cylinder and turn it clockwise approximately 3/4 turn to release the lock. Pull the lock cylinder out until it stops and remove the lock from the King Pin.

The **King Pin Lock** requires little maintenance. If the lock is exposed to the elements for a long period of time, it may be necessary to clean and lubricate the lock with a high quality lock lubricant such

as  available at [www.mil-comm.com](http://www.mil-comm.com).

